



CHARACTERISITICS

Operating Force:	1809f Max.
Release Force:	209f Min.
Operation Position:	5.4±0.3mm.
Pre Travel:	0.65~1.5mm
Differential Travel:	0.25mm Max.
Over Travel:	0.7mm Min.
Free Position:	6.43mm Max.
Total Travel Position:	4.4mm Max.

ELECTRICAL DATA

CONTACT ARRANGEMENT	SWITCH SEALING	TERMINALS
S,P,D,T	IP67	IP00

Rating

0.1 A 48VDC 125/250VAC
3A 12VDC
M40T85 1E5

A4				
A3				
A2				
A1				
REV.	DATE	REVISION	DESCRIPTION	ISSUE
		A		B



COMMON TOLERANCE:

X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED		PRODUCT NAME:
DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TG303-130S00A13
DATE	2017	APPROVAL BY	ALEN	Https: www.rocpu.tw
ROC PU TECHNOLOGY CO.,LTD				
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				